
Manual English

FRUNK.LY Maker Kit

Model 3

In the box

- ☐ **A** 2 base frames with folding hinges
- ☐ 1 bag with screws and small parts
  - ☐ **B** 2 short screws with handle
  - ☐ **C** 2 long screws with handle and nut
  - ☐ **D** 2 U-brackets
  - ☐ **E** 2 catch pins
  - ☐ **F** Screws for the U-brackets and catch pins
  - ☐ **G** 1 Tesla-style keychain
- ☐ **H** 1 spare parts bag with 2 U-brackets



A 2×



D 2×



E 2×


You also need: an open-end wrench (10 mm) and your own tabletop.

For inspiration: fitting the LT, with photos
frunk.ly/q/mk-3-en

Installation · Base frames

1 Empty the frunk completely.

2 There are two screws in the floor of the frunk. Loosen them with your wrench (10 mm), counterclockwise, and take them out. Keep them safe: they go back in once the base frames are removed.



3 Place the left base frame (A) in the frunk so that its hole sits over the hole in the floor.

4 Fix it with a short screw with handle (B).


⚠ **Hand tight only.**

5 Repeat steps 3 and 4 with the right base frame.

Building the tabletop · U-brackets

> **Our recommendation:** 70 × 40 cm, 12 mm birch plywood. The measurements in the diagram are for this size.

6 Screw the two U-brackets (D) to the underside of your tabletop, following the measurements in the diagram.



- Windshield
- Catch pin
- U-bracket
- Guide value
- You stand here


Building the tabletop · Catch pins

7 Screw on the two catch pins (E): the small metal pins that click into the ball catches and hold the table more firmly. Check their position with the U-brackets in place. Orientation and spacing decide whether the table folds and clicks in properly.


Installation · Tabletop

8 Remove the transport locks from the hinges and fold the hinges out one by one.

9 Lay the tabletop on the hinges and line up the U-brackets with the holes on top of the hinges.



10 Take the nuts off the long screws (C). Push one screw through the U-bracket and the hinge on each side and screw the nut on.



⚠ **Don't tighten it, or the tabletop will no longer fold.**

Done.

Removal

Work in reverse order, then screw the two original screws back into the frunk floor.

⚠ **Don't overtighten.**

Everyday use

Unfold: Open the frunk. Take the tabletop by its left and right sides and pull it up and towards you. The hinges fold up with it.

Fold away: Take the tabletop by its left and right sides again. Push it back towards the windshield; it lowers as the hinges fold in. Guide it down until it lies flat, then close the frunk.

Storage underneath: The frunk stays usable with the table fitted. Take the folded tabletop by its back edge, towards the windshield, which is also where the latch sits. Tilt it towards you: it then hangs open towards the front of the car, and you reach past it into the frunk.

⚠ Safety information

Load: The table holds up to 10 kg, evenly distributed. Do not sit on it, lean on it or pull yourself up on it.

After a knock: If you bump the tabletop, check that it is still secure.

Cargo: The driver is responsible for the load and for securing it. The base frames are fixed in the frunk with the screws with handle; the tabletop's shape keeps it from sliding.

Pinching: Fingers can get caught when the hinges fold open or shut. Mind your hands.

Spare parts bag: If one of the two U-brackets under the tabletop breaks, swap it for a spare. It is held by 4 Torx screws.

Questions or spare parts? support@frunk.ly

Manufacturer: Frunkly · Peter Amelang
Narzissenweg 14, 22047 Hamburg, Germany
support@frunk.ly · frunk.ly

Maker Kit · Model 3 · EN · Version 10/2026